

Swissphone DE925

The digital pager for the highest demands



The most important performance features

- > 5-line backlit full graphic LC Display with over 100 characters
- > 32 RIC, each with 4 subaddresses
- > 9 alerts/user profiles plus 1 extension
- > IP54* protection class for daily use in all weather conditions
- > longer independent battery operation thanks to ECO mode
- > Self-explanatory menu structure

))) Introducing the logical next step up from the DE920: the DE925. Designed to meet the needs of more demanding users still, its full graphic display ensures multiple compatibility and gives the user the option of displaying messages in either the 16-character format (and thereby compatible with Swissphone DE900/920 pagers) or in 20 or 21-character display format. This means that the pager is flexible and can be integrated in alarm signal networks optimised for a prescribed character-per-line specification.

))) And that's not all: Swissphone has also enlarged the display from three to five lines. When a message is opened, the status line is deactivated and the space used as a fifth line for the message display. This makes a total text display size of up to 105 characters available to the user. Operating, too, has been revised and configured even more ergonomically, for full professional functionality that is intuitive and secure to operate. Guaranteed to meet the highest demands.



DE925

performance features	DE925
Frequency bands	VHF 138 - 174 MHz (2m band) UHF 450 - 470 MHz (70cm band) (other frequencies on request)
Channel spacing	12.5 / 20/25 kHz
Sensitivity (best position) @ baudrate 512 bit/s @ baudrate 1200 bit/s @ baudrate 2400 bit/s	3.5 µV/m 3.5 µV/m 4.0 µV/m
Frequency processing	PLL VHF: +/- 0.5 MHz Adjustment range UHF: +/- 1.0 MHz Adjustment range
Compliance	TR-BOS (DME II), ETSI EN 300 390
Norms	IEC 60068-2-27 (shock), IEC 60069-2-6 (vibration), IEC 60068-2-32 (drop test), IEC 60529:1991 + A1:2000 (IP 52*) *IP54 ensured with leather carry bag LH900 (see Swissphone accessories)
Addresses	32 RIC (128 subaddresses) frame independent
Display	full graphic display: Possible display types (line x characters) 5 x 16, 5 x 20, 5 x 21
Alerting	- acoustic > 80dB(A) @30cm distance - 9 alers/user profiles + 1 extension - vibrator
Messages	- 15 messages of up to 255 characters stored with time and date - up to 2 message folders and automatic storage tray, altogether 4096 characters storable - 128 pre-programmed messages of up to 32 characters
Power management	- Type AA battery - operating time left (regular mode/ECO mode) dry cell (1.5V) 810 / 950 h NiMH rechargeable (2200 mAh) 670 / 760 h NiCd rechargeable (800 mAh) 230 / 285 h
Case (H x W x D), Weight	in mm 78 x 53 x 24 in inch 3.1 x 2.1 x 0.95 97 g (3.42 oz.) with battery
Miscellaneous	- supports on-air programming - Option IDEA® 128 bit encrypting

Specifications subject to change

Additional information: www.swissphone.com



Swissphone Telecom AG
Fältnisstrasse 21, CH-8833 Samstagern
Tel. +41 44 786 77 70, Fax +41 44 786 77 71
www.swissphone.com

Your Swissphone-partner:

För mer information om denna produkt, vänligen kontakta:

Celab
COMMUNICATIONS AB

Rollsbovägen 20
442 40, Kungälv, Sverige
Tel: + 46 (0)303 24 60 00
Fax: + 46 (0)303 939 91
info@celab.se
www.celab.se